



# NDMS

Features	Benefits
<ul style="list-style-type: none"> <li>• Very high void in tread pattern</li> </ul>	<ul style="list-style-type: none"> <li>• Good traction on soft and sandy terrain</li> <li>• All wheel fitment</li> </ul>

TYRE SIZE	PLY RATING	REC-RIM WIDTH (Code)	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	NON-SKID DEPTH (mm)	LOAD/INFLATION		STATIC LOADED Radius (mm)	FLAP CODE	TUBE VALVE CODE
						SINGLE kgs@kgs/sq.cm	DUAL kgs@kgs/sq.cm			
9.00-16	10	6.00T	245	905	15.7	1530@4.25	-	425	16M	TR 76A DBV
9.00-16*	10	6.50H	250	905	15.7	1530@4.25	-	425	16N	TR 76A DBV
8.25-20	10	6.5	235	980	14.5	1835@6.00	1610@5.25	462	20M	TR 175A
8.25-20	12	6.5	235	980	14.5	2040@7.05	1790@6.30	462	20M	TR 175A
9.00-20	12	7.0	252	1014	15.4	2335@6.70	2050@6.00	479	20N	TR 175A
11.00-20	14	8.0	305	1100	16.7	2990@7.05	2620@6.30	513	20RR	TR 78A
11.00-20	16	8.0	305	1100	16.7	3265@8.10	2865@7.40	513	20RR	TR 78A
12.00-20	16	8.5	320	1140	17.8	3510@7.40	3080@6.70	532	20RR	TR 78A

\*5 Degree Taper Bead